




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : C10G 45/00, 65/12	A1	(11) International Publication Number: WO 00/34416 (43) International Publication Date: 15 June 2000 (15.06.00)
(21) International Application Number: PCT/US99/28790 (22) International Filing Date: 7 December 1999 (07.12.99) (30) Priority Data: 60/111,345 8 December 1998 (08.12.98) US (71) Applicant: EXXON RESEARCH AND ENGINEERING COMPANY [US/US]; P.O. Box 390, 180 Park Avenue, Florham Park, NJ 07932-0390 (US). (72) Inventors: ELLIS, Edward, Stanley; 39 Rankin Avenue, Basking Ridge, NJ 07920 (US). JUNG, Henry; 35 Wexford Drive, Mendham, NJ 07945 (US). LEWIS, William, Ernest; 6933 North Fieldgate Court, Baton Rouge, LA 70808 (US). (74) Agents: NAYLOR, Henry, E. et al.; Exxon Research and Engineering Company, P.O. Box 390, Florham Park, NJ 07932-0390 (US).		(81) Designated States: AL, AU, BA, BB, BG, BR, CA, CN, CU, CZ, EE, GE, HR, HU, ID, IL, IN, IS, JP, KP, KR, LC, LK, LR, LT, LV, MG, MK, MN, MX, NO, NZ, PL, RO, RU, SG, SI, SK, SL, TR, TT, UA, UZ, VN, YU, ZA, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>

(54) Title: PRODUCTION OF LOW SULFUR/LOW AROMATICS DISTILLATES**(57) Abstract**

A process for hydroprocessing a hydrotreated liquid distillate where the feedstream is fed to reaction vessel (R1) via line (10) along with a hydrogen-containing treat gas via line (12). A combined liquid phase and vapor phase product stream exit reaction vessel (R1) via line (16). The vapor phase product stream is collected overhead via line (20). The liquid reaction product is passed to reaction vessel (R2) via line (20) and passed downwardly through the reaction zones (22a) and (22b) or reaction zone (R2).

PRODUCTION OF LOW SULFUR/LOW AROMATICS DISTILLATES

BACKGROUND OF THE DISCLOSURE

FIELD OF THE INVENTION

The present invention relates to a process for hydroprocessing a hydrotreated liquid distillate stream to produce a stream exceptionally low in sulfur as well as aromatics. A hydrotreated distillate stream is further hydrotreated in a co-current reaction zone wherein the reaction product is passed to a separation drum wherein a vapor product is collected overhead and a liquid product is passed to an aromatics saturation zone countercurrent to the flow of hydrogen treat gas.

BACKGROUND OF THE INVENTION

Environmental and regulatory initiatives are requiring ever lower levels of both sulfur and aromatics in distillate fuels. For example, proposed sulfur limits for distillate fuels marketed in the European Union for the year 2005 is 50 wppm or less. There are also regulations that will require lower levels of total aromatics in hydrocarbons and, more specifically, the multiring aromatics found in distillate fuels and heavier hydrocarbon products. Further, the maximum allowable aromatics level for U.S. on-road diesel, CARB reference diesel and Swedish Class I diesel are 35, 10 and 5 vol.%, respectively. Further, the CARB and Swedish Class I diesel fuels allow no more than 1.4 and 0.02 vol.% polyaromatics, respectively.

Much work is presently being done in hydrotreating because of greater demands for the removal of heteroatoms, most notably sulfur, from transportation and heating fuel streams. Hydrotreating, or in the case of sulfur

- 2 -

removal, hydrodesulfurization, is well known in the art and usually requires treating the petroleum streams with hydrogen in the presence of a supported catalyst at hydrotreating conditions. The catalyst is typically comprised of a Group VI metal with one or more Group VIII metals as promoters on a refractory support. Hydrotreating catalysts which are particularly suitable for hydrodesulfurization and hydrodenitrogenation generally contain molybdenum or tungsten on alumina promoted with a metal such as cobalt, nickel, iron, or a combination thereof. Cobalt promoted molybdenum on alumina, and nickel promoted molybdenum on alumina catalysts are most widely used when the limiting specifications are hydrodesulfurization, while nickel promoted molybdenum on alumina catalysts are the most widely used for hydrodenitrogenation and partial aromatic saturation.

Much work is being done to develop more active catalysts and improved reaction vessel designs in order to meet the demand for more effective hydroprocessing processes. Various improved hardware configurations have been suggested. One such configuration is a countercurrent design wherein the feedstock flows downward through successive catalyst beds counter to upflowing treat gas, which is typically a hydrogen containing treat-gas. The downstream catalyst beds, relative to the flow of feed can contain high performance, but otherwise more sulfur sensitive catalysts because the upflowing treat gas carries away heteroatom components such as H_2S and NH_3 that are deleterious to the sulfur and nitrogen sensitive catalysts. While such countercurrent reactors have commercial potential, they never-the-less are susceptible to flooding. That is, where upflowing treat gas and gaseous products impede the downward flow of feed. Such flooding tendency is increased with increases in treat gas rate.

Other process configurations include the use of multiple reaction stages, either in a single reaction vessel, or in separate reaction vessels. More

- 4 -

second stage herein, said first reaction stage containing one or more reaction zones operated at hydrodesulfurization conditions wherein each reaction zone contains a bed of hydrotreating catalyst;

- b) passing the resulting reactant to a separation zone wherein a vapor phase stream and a liquid phase stream are produced;
- c) collecting said vapor phase stream overhead; and
- d) passing said liquid phase stream to a second reaction stage in the presence of a hydrogen-containing treat gas, said reaction stage containing one or more reaction zones operated at aromatics saturation conditions wherein each reaction zone contains a bed of aromatics saturation catalyst, and wherein said hydrogen-containing treat gas is passed through said reaction stage countercurrent to the flow of said liquid phase stream.

In a preferred embodiment of the present invention, the liquid phase stream, before it passes through said second reaction stage is contacted with a vapor to strip dissolved gases from the liquid phase.

BRIEF DESCRIPTION OF THE FIGURE

The figure hereof shows multiple reaction vessels of the present invention showing separation of the liquid phase product from the vapor phase product and further processing of the liquid phase product stream in an aromatics saturation stage.

DETAILED DESCRIPTION OF THE INVENTION

Feedstocks suitable for being treated by the present invention are those petroleum based feedstocks boiling in the distillate range and above and which have previously been hydrotreated to reduce the sulfur and nitrogen levels. Typical sulfur levels in such hydrotreated distillates are in the range of less than

- 5 -

about 3,000 wppm, more preferably to less than about 1,000 wppm, most preferably to less than about 500 wppm sulfur, ideally to less than about 350 wppm. Non-limiting examples of such feeds include diesel fuels, jet fuels, heating oils, and lubes. Such feeds typically have a boiling range from about 150 to about 600°C, preferably from about 175 to about 400°C. It is highly desirable for the refiner to upgrade these types of feedstocks by removing as much of the sulfur as possible, as well as to saturate aromatic compounds.

The process of the present invention can be better understood by a description of a preferred embodiment illustrated by Figure 1 hereof. The current invention offers an improvement over the prior art by using only once through hydrogen treat gas. For purposes of discussion, the first reaction stage R1 is a hydrotreating stage to further reduce the level of sulfur and nitrogen, and the second reaction stage R2 is an aromatics saturation stage. The hydrogen reacts with the impurities to convert them to H_2S , NH_3 , and water vapor, which are removed as part of the vapor effluent, and it also saturates olefins and aromatics. Miscellaneous reaction vessel internals, valves, pumps, thermocouples, and heat transfer devices etc. are not shown for simplicity. Figure 1 shows reaction vessel R1 which contains reaction zones 10a and 10b, each of which is comprised of a bed of hydrotreating catalyst, although only a single or more than two reaction zones can be employed. It is preferred that the catalyst be in the reactor as a fixed bed, although other types of catalyst arrangements can be used, such as slurry or ebullating beds. Downstream of each reaction zone is a non-reaction zone 12 a and 12b. The non-reaction zone is typically void of catalyst, that is, it will be an empty section in the vessel with respect to catalyst. Although not shown, there may also be provided a liquid distribution means upstream of each reaction stage. The type of liquid distribution means is believed not to limit the practice of the present invention, but a tray arrangement is preferred, such as sieve trays, bubble cap trays, or trays

- 6 -

with spray nozzles, chimneys, tubes, etc. A vapor-liquid mixing device (not shown) can also be employed in non-reaction zone 12a for the purpose of introducing a quench fluid (liquid or vapor) for temperature control.

The feedstream is fed to reaction vessel R1 via line 10 along with a hydrogen-containing treat gas via line 12. The hydrogen-containing treat gas is cascaded from reaction stage R2. Make up hydrogen-containing treat gas can also be added via line 14. It is preferred that the rate of introduction of treat gas be less than or equal to 3 times the chemical hydrogen consumption of the reactions in both stages, more preferably less than about 2 times, and most preferably less than about 1.5 times. The feedstream and hydrogen-containing treat gas pass, cocurrently, through the one or more reaction zones of reaction vessel R1, which represents the first reaction stage wherein the feedstream is further hydrotreated to remove substantially all of the heteroatoms from the feedstream. It is preferred that the first reaction stage contain a Co-Mo, or Ni-Mo, on refractory support catalyst, and a downstream reaction stage contain a Ni-Mo on refractory support catalyst.

The term "hydrotreating" as used herein refers to processes wherein a hydrogen-containing treat gas is used in the presence of a suitable catalyst which is primarily active for the removal of heteroatoms, such as sulfur, and nitrogen, and for some hydrogenation of aromatics. Suitable hydrotreating catalysts for use in the present invention are any conventional hydrotreating catalyst and includes those which are comprised of at least one Group VIII metal, preferably Fe, Co and Ni, more preferably Co and/or Ni, and most preferably Co; and at least one Group VI metal, preferably Mo and W, more preferably Mo, on a high surface area support material, preferably alumina. Other suitable hydrotreating catalyst supports include zeolites, amorphous silica-alumina, and titania-alumina. Noble metal catalysts can also be employed, preferably when

- 7 -

the noble metal is selected from Pd and Pt. It is within the scope of the present invention that more than one type of hydrotreating catalyst be used in the same reaction vessel. The Group VIII metal is typically present in an amount ranging from about 2 to 20 wt.%, preferably from about 4 to 12%. The Group VI metal will typically be present in an amount ranging from about 5 to 50 wt.%, preferably from about 10 to 40 wt.%, and more preferably from about 20 to 30 wt.%. All metals weight percents are on support. By "on support" we mean that the percents are based on the weight of the support. For example, if the support were to weigh 100 g, then 20 wt.% Group VIII metal would mean that 20 g. of Group VIII metal was on the support. Typical hydrotreating temperatures range from about 100°C to about 400°C with pressures from about 50 psig to about 3,000 psig, preferably from about 50 psig to about 2,500 psig.

A combined liquid phase and vapor phase product stream exit reaction vessel R1 via line 16 and into separation zone S wherein a liquid phase product stream is separated from a vapor phase product stream. The liquid phase product stream will typically be one that has components boiling in the range from about 150°C to about 650°C, but will not have a boiling range greater than the feedstream. The vapor phase product stream is collected overhead via line 20.

The liquid reaction product from separation zone S is passed to reaction vessel R2 via line 20 and is passed downwardly through the reaction zones 22a and 22b of reaction stage R2. Prior to being passed downwardly through reaction stage R2, said liquid reaction product stream can first be contacted in a stripping zone to remove entrapped vapor components from the liquid stream. For example, as the liquid product stream flows through the stripping zone, it is contacted by upflowing hydrogen-containing treat gas under conditions effective for transferring at least a portion of the feed impurities in the

vapor into the liquid. The contacting means comprises any known vapor- liquid contacting means, such as rashig rings, berl saddles, wire mesh, ribbon, open honeycomb, gas-liquid contacting trays, such as bubble cap trays and other devices, etc.

Fresh hydrogen-containing treat gas is introduced into reaction stage R2 via line 24 and is passed in an upward direction counter to the flow of liquid reaction product. The introduction of clean treat gas (gas substantially free of H_2S and NH_3) allows reaction stage R2 to be operated more efficiently owing to a reduction in the activity suppression effects on the catalyst exerted by H_2S and NH_3 and an increase in H_2 partial pressure. This type of two stage operation is particularly attractive for very deep removal of sulfur and nitrogen or when a more sensitive catalyst (i.e., hydrocracking, aromatic saturation, etc) is used in the second reactor. Another advantage of the present invention is that the treat gas rate is relatively low compared with more conventional processes. The use of relatively low treat gas rates is primarily due to the use of previously hydrotreated distillate feedstocks. Further efficiencies are gained by not requiring recycle of treat gas.

The liquid/vapor separation step (S) may be a simple flash or may involve the addition of stripping steam or gas to improve the removal of H_2S and NH_3 . The liquid stream and treat gas are passed countercurrent to each other through one or more catalyst beds, or reaction zones, 22a and 22b. The resulting liquid product stream exits reaction stage R2 via line 26, and a hydrogen-containing vapor product stream exits reaction stage R2 and is cascaded to reaction stage R1. Reaction stage R2 also contains non reaction zones 23a and 23b following each reaction zones. The catalyst in this second reaction stage is an aromatic saturation catalyst.

The figure also shows several options. For example, lines 30 and 32 can carry kerosene which can be used as a quench fluid. Also, a unsaturated feedstock can also be introduced into the first reaction stage via line 28. The degree of unsaturation can be up to about 50 wt.%.

The reaction stages used in the practice of the present invention are operated at suitable temperatures and pressures for the desired reaction. For example, typical hydroprocessing temperatures will range from about 40°C to about 450°C at pressures from about 50 psig to about 3,000 psig, preferably 50 to 2,500 psig.

For purposes of hydroprocessing and in the context of the invention, the terms "hydrogen" and "hydrogen-containing treat gas" are synonymous and may be either pure hydrogen or a hydrogen-containing treat gas which is a treat gas stream containing hydrogen in an amount at least sufficient for the intended reaction, plus other gas or gasses (e.g., nitrogen and light hydrocarbons such as methane) which will not adversely interfere with or affect either the reactions or the products. Impurities, such as H₂S and NH₃ are undesirable and, if present in significant amounts, will normally be removed from the treat gas, before it is fed into the reactor. The treat gas stream introduced into a reaction stage will preferably contain at least about 50 vol. %, more preferably at least about 75 vol. % hydrogen, and most preferably at least 95 vol. %. In operations in which unreacted hydrogen in the vapor effluent of any particular stage is used for hydroprocessing in any stage, there must be sufficient hydrogen present in the fresh treat gas introduced into that stage, for the vapor effluent of that stage to contain sufficient hydrogen for the subsequent stage or stages. It is preferred in the practice of the invention, that all or a portion of the hydrogen required for the first stage hydroprocessing be contained in the second stage vapor effluent fed up into the first stage. The first stage

vapor effluent will be cooled to condense and recover the hydrotreated and relatively clean, heavier (e.g., C₄-C₅+) hydrocarbons.

Non-limiting examples of aromatic hydrogenation catalysts include nickel, cobalt-molybdenum, nickel-molybdenum, and nickel-tungsten. Noble metal containing catalysts can also be used. Non-limiting examples of noble metal catalysts include those based on platinum and/or palladium, which is preferably supported on a suitable support material, typically a refractory oxide material such as alumina, silica, alumina-silica, kieselguhr, diatomaceous earth, magnesia, and zirconia. Zeolitic supports can also be used. Such catalysts are typically susceptible to sulfur and nitrogen inhibition or poisoning. The aromatic saturation stage is preferably operated at a temperature from about 40°C to about 400°C, more preferably from about 200°C to about 350°C, at a pressure from about 100 psig to about 3,000 psig, preferably from about 200 psig to about 1,200 psig, and at a liquid hourly space velocity (LHSV) of from about 0.3 V/V/Hr. to about 10 V/V/Hr, preferably from about 1 to 5 V/V/Hr.

The liquid phase in the reaction vessels used in the present invention will typically consist primarily of the higher boiling point components of the feed. The vapor phase will typically be a mixture of hydrogen-containing treat gas, heteroatom impurities like H₂S and NH₃, and vaporized lower-boiling components in the fresh feed, as well as light products of hydroprocessing reactions. If the vapor phase effluent still requires further hydroprocessing, it can be passed to a vapor phase reaction stage containing additional hydroprocessing catalyst and subjected to suitable hydroprocessing conditions for further reaction. Alternatively, the hydrocarbons in the vapor phase products can be condensed via cooling of the vapors, with the resulting condensate liquid being recycled to either of the reaction stages, if necessary. It is also within the scope of the present invention that a feedstock which already contains adequately

- 11 -

low levels of heteroatoms be fed directly into the reaction stage for aromatic saturation and/or cracking

The present invention can be better understood by reference to the following example that is present for illustrative purposes only and is not to be taken as limiting the invention in any way.

CLAIMS:

1. A two stage process for hydroprocessing a hydrotreated distillate feedstock which process comprises:

a) reacting said feedstock in a first reaction stage in the presence of a hydrogen-containing treat gas cascaded from the second reaction stage herein, said first reaction stage containing one or more reaction zones operated at hydrodesulfurization conditions wherein each reaction zone contains a bed of hydrotreating catalyst;

b) passing the resulting reactant to a separation zone wherein a vapor phase stream and a liquid phase stream are produced;

c) collecting said vapor phase stream overhead; and

d) passing said liquid phase stream to a second reaction stage in the presence of a hydrogen-containing treat gas, said reaction stage containing one or more reaction zones operated at aromatics saturation conditions wherein each reaction zone contains a bed of aromatics saturation catalyst, and wherein said hydrogen-containing treat gas is passed through said reaction stage countercurrent to the flow of said liquid phase stream.

2. The process of claim 1 wherein the liquid phase stream, before it passes through said second reaction stage is stripped to reduce its content of dissolved vapor phase product by contacting the liquid with a stripping gas.

3. The process of claim 2 wherein the stripping gas is the vapor phase product from the second reaction stage.

- 13 -

4. The process of claim 3 wherein the stripping gas and liquid was contacted in a vapor/liquid contacting zone which is vertically disposed above the second reaction zone.

5. The process of claim 4 wherein the vapor/liquid contacting zone comprises a countercurrent flow contacting zone in which vapor flows counter to the downward flowing liquid.

6. The process of claim 1 wherein the vapor phase stream from the first reaction stage is cooled and the resulting condensed liquid stream is separated from the remaining uncondensed stream, and a portion of the condensed liquid stream is combined with the liquid feed to the first reaction stage.


7. The process of claim 1 wherein the vapor phase stream from the first reaction stage is cooled and the resulting condensed liquid stream is separated from the remaining uncondensed stream, and a portion of the condensed liquid stream is combined with the liquid feed to the second reaction stage.

8. The process of claim 1 wherein the vapor phase stream from the first reaction stage is cooled and the resulting condensed liquid stream is separated from the remaining uncondensed stream, and a portion of the condensed liquid stream is used as a quench liquid between two or more of the reaction zones of the first or second reaction stage.

9. The process of claim 4 wherein the first reaction stage is vertically disposed above the vapor/liquid contacting zone.

10. The process of claim 9 wherein the liquid feedstock flows downward through said one or more reaction zones to said hydrogen-containing treat gas.

11. The process of claim 1 wherein the hydrogen-containing treat gas is cascaded from the vapor/liquid contacting zone of claim 4.



INTERNATIONAL SEARCH REPORT

International application No.
PCT/US99/28790

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : C10G 45/00; 65/12

US CL : 208/210 ,143

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 208/210 ,143

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EAST

search terms:aromaticadj saturation , hydrodesulfS, countercurrent

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4,021,330 A (SACHELL, JR) 03 May 1977, col 2.. lines 16-49	1-11
X	US 5114,562 A (HAUN, et al)19 May 1992, col 2, lines 44-64.	1-11



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
B earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*A* document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

23 FEBRUARY 2000

Date of mailing of the international search report

07 MAR 2000

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

HELANE MYERS

Telephone No. (703) 308-0661